



Product data sheet

HASXS4T0110G

Characteristics

Soft starter for asynchronous motor, HASXS, 11kW, 3PH, 400V

	Main	
	Range of product	HASXS
	Product or component type	Soft starter
	Product destination	Asynchronous motors
	Product specific application	Fan, pump, compressor, conveyor Complex and advanced machines
	Network number of phases	3 phases
	[Us] rated supply voltage	380...440 V AC 50...60 Hz
	Motor power kW	11 kW, 3 phases at 380...440 V
	Motor power hp	15 hp, 3 phases at 380...440 V
	IcL starter rating	25 A
	Utilisation category	AC-53B
	Type of start	Start with voltage ramp
Complementary		
Assembly style	Enclosed	
Function available	With integrated bypass	
Output voltage	= power supply voltage	
Starting time	Adjustable from 2 to 100 s / 12	
Deceleration time symb	Adjustable from 1 to 50 s	
Discrete input type	Internal (RET) reset Internal (EMS) emergency stop Internal (STOP) stop Internal (RUN) run	
Discrete output current	5 A AC	
Marking	CE	
Type of cooling	AF (air forced)	
Communication port protocol	Modbus	
Height	150 mm	
Width	264 mm	
Depth	170 mm	
Net weight	3.3 kg	
Environment		
IP degree of protection	IP20	
Vibration resistance	5.9 m/s²	
Relative humidity	0...90 % without condensation or dripping water	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...65 °C
Operating altitude	= 1000 m without derating > 1000 m with current derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty