

Product data sheet



HAVSP4T0300P

Characteristics

Variable speed drive, SMART Pump, 30 kW, 380-480V, 3 phase, normal duty

	Main	
	Range of product	SMART-Pump
	Product or component type	Variable speed drive
	Product specific application	Pump Fan Chiller
	Network number of phases	3 phases
	[Us] rated supply voltage	380...480 V - 15...10 %
	Supply frequency	50...60 Hz
	Motor power kW	30 kW for normal duty
	Motor power hp	40 hp for normal duty
	Maximum transient current	72 A during 1 min (normal duty) 90 A during 1 s (normal duty) 108 A during 0 s (normal duty)
	Asynchronous motor control profile	Sensorless vector control (SVC) Voltage/frequency ratio (V/f)
	Speed drive output frequency	0...599 Hz
	Continuous output current	60 A
	EMC filter	Class C3 EMC filter

Complementary

Product destination	Asynchronous motors
Function available	Multi-pump control Dry run protection Energy/flow calculator Frost and condensation protection Pump cleaning Fire override mode Energy saving mode
Type of cooling	Fan
Communication port protocol	Modbus
Regulation loop	Adjustible PID regulator with sleep mode
Acceleration and deceleration ramps	Linear adjustable separately from 0.01 to 3600 s
Frequency resolution	Digital input: 0.005/50 Hz Analog input: 0.05/50 Hz
Analogue input number	2
Analogue input type	AI1 voltage: 0...10 V, impedance: 100 kOhm, resolution 0.01 V AI1 current: 0...20 mA, impedance: 500 Ohm, resolution 0.02 mA AI2 voltage: 0...10 V, impedance: 100 kOhm, resolution 0.01 V AI2 current: 0...20 mA, impedance: 500 Ohm, resolution 0.02 mA
Discrete input number	5
Discrete input type	Programmable (DI1...DI5) Programmable as pulse input (DI5)
Analogue output number	2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Analogue output type	AO1 voltage/current: 0...20 mA or 0...10 V AO2 voltage/current: 0...20 mA or 0...10 V
Discrete output number	3
Discrete output type	configurable relay logic 250 V (5 A) for NO relay output circuit configurable relay logic 250 V (3 A) for NC relay output circuit configurable relay logic 24 V DC (3 A) for NO relay output circuit configurable relay logic 24 V DC (3 A) for NC relay output circuit open collector 9...30 V (50 mA) open collector 9...30 V (50 mA) for pulse output
Output frequency	50 kHz for pulse output at DO2
Display type	5 digits 7 segments for 38 parameters
Device application	Speed control
Type of installation	Indoor/outdoor
Control type	Manual using keypad Using control terminal Using serial port
Device mounting	Wall mounted Enclosure Flange
Speed accuracy	+/- 0.1 % of nominal speed
Protection type	Hammer effect Overcurrent Overvoltage Undervoltage Overheating Overload Short-circuit
Width	235 mm
Height	370 mm
Depth	235 mm

Environment

Relative humidity	0...95 % without condensation
Ambient air temperature for storage	-20...60 °C
Quality labels	CE
Operating altitude	= 1000 m
IP degree of protection	IP20
Ambient air temperature for operation	-10...40 °C
Environmental characteristic	Dust resistant Corrosive gas free Oil and vapour resistant
Vibration resistance	5.9 m/s²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	370 mm
Package 1 Width	235 mm
Package 1 Length	235 mm
Package 1 Weight	11 kg