



Product data sheet

HDB3VR232TC

Characteristics

Residual current switch HDB3VR - 2P - 32A - 300mA - for AC



Main

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Range of product               | HDB3VR                                  |
| Product or component type      | Residual current circuit breaker (RCCB) |
| Poles description              | 2P                                      |
| Earth-leakage protection class | Class AC                                |

Complementary

|                                |                                         |
|--------------------------------|-----------------------------------------|
| [In] rated current             | 32.0 A                                  |
| Earth-leakage sensitivity      | 300.0 mA                                |
| Frame size                     | 63AF                                    |
| [Ue] rated operational voltage | 230 V AC                                |
| [Ui] rated insulation voltage  | 500 V                                   |
| Mechanical durability          | 2000 cycles                             |
| Electrical durability          | 1000 cycles                             |
| Protection type                | Earth-leakage protection direct contact |
| Local signalling               | Mechanical indicator for fault          |
| Mounting support               | 35 mm DIN rail                          |
| 9 mm pitches                   | 4                                       |
| Clamping connection capacity   | = 25 mm²                                |
| Tightening torque              | 2...4.5 N.m                             |
| Height                         | 78.5 mm                                 |
| Width                          | 36.0 mm                                 |
| Depth                          | 70.0 mm                                 |
| Embedding depth                | 43.5 mm                                 |
| E-commerce address             | Residual-current-switch-hdb3vr-ac-type  |

Environment

|                                       |                |
|---------------------------------------|----------------|
| Environmental characteristic          | Fire retardant |
| Tropicalisation                       | 2              |
| Pollution degree                      | 2              |
| Ambient air temperature for operation | -25...40 °C    |
| Standards                             | EN/IEC 61008-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product certifications

TÜV  
CE  
CB

Offer Sustainability

Sustainable packaging

No