



Product data sheet

HDB3VR425YA

Characteristics

Residual current switch HDB3VR - 4P - 25A - 100mA - for AC & DC

	
Main	
Range of product	HDB3VR
Product or component type	Residual current circuit breaker (RCCB)
Poles description	4P
Earth-leakage protection class	Class A

Complementary

[In] rated current	25.0 A
Earth-leakage sensitivity	100.0 mA
Frame size	63AF
[Ue] rated operational voltage	400 V AC
[Ui] rated insulation voltage	500 V
Mechanical durability	2000 cycles
Electrical durability	1000 cycles
Protection type	Earth-leakage protection direct contact
Local signalling	Mechanical indicator for fault
Mounting support	35 mm DIN rail
9 mm pitches	8
Clamping connection capacity	= 25 mm²
Tightening torque	2...4.5 N.m
Height	78.5 mm
Width	72.0 mm
Depth	70.0 mm
Embedding depth	43.5 mm
E-commerce address	Hdb3vr225sc

Environment

Environmental characteristic	Fire retardant
Tropicalisation	2
Pollution degree	2
Ambient air temperature for operation	-25...40 °C
Standards	EN/IEC 61008-1

Product certifications

TÜV
CE
CB

Offer Sustainability

Sustainable packaging

No